

Camden Introduces the Next Generation of Pre Load Strikes!

CAMDEN'S NEW 20 SERIES PRE LOAD electric strikes eliminate binding problems when the door latch is forced against the strike keeper. Whether caused by differences in inside/outside air pressure or warped doors, 20 Series strikes offer the highest pre load rating, precision engineered quality and adjustability in the industry.

- Pre load (Fail secure only)
AC 12-24V; 20 lbs., DC 12V; 40 lbs.,
DC 24V; 65 lbs.
- Standard body model with selection
of 4 faceplates
- EZ FIT™ 'no cut' model CX-EPD2850L
with both vertical and horizontal
faceplate adjustment
- Adjustable keeper
- Latch monitoring, standard
- Static strength 1,500 lbs.
- Selectable 12/24V AC/DC
- Selectable fail safe/fail secure
- 1/2" to 5/8" latch projection (Throw)
- For cylindrical locksets and
centerline mortise locks
- 5 year warranty



A COMPLETE LINE OF ELECTRIC STRIKES FOR CYLINDRICAL LOCKSETS



Series 10 & 18
(EZ FIT)™
BHMA 1



Series 14
FIRE RATED
BHMA 1



Series 20
Pre Load (EZ FIT)™
BHMA 2



Series 30
ADJUSTABLE KEEPER
BHMA 3









Discover the best in door activating and locking products!

TOLL FREE: 1.877.226.3369 Tel: 905.366.3377 Fax: 905.366.3378
info@camdencontrols.com www.camdencontrols.com



CAMDEN PRECISION ENGINEERED ELECTRIC DOOR STRIKES

			STRIKE ONLY	STRIKES COMPLETE WITH FACEPLATE				
				ANSI Square 4 7/8" x 1 1/4"	ANSI Round 4 7/8" x 1 1/4"	Hollow Metal Door 6 7/8" x 1 1/4"	Wood Door 7 15/16" x 1 1/4"	
SERIES 10 & 18 (EZ FIT)™ - BHMA GRADE 1 STRIKE			Description	Model	Model	Model	Model	Model
	<p>Designed for heavy-duty applications. Accommodates cylindrical locksets with a 5/8" to 3/4" throw (3/4" requires 1/8" door gap) in aluminum, wood or metal frames.</p> <p>EZ FIT™ model installs in standard ANSI strike plate, and is both vertically and horizontally adjustable.</p>	<ul style="list-style-type: none"> UL 1034 burglary-resistant Field selectable fail secure and fail safe Dual voltage 12/24V AC/DC Fully reversible for right or left-hand doors Latch monitoring (option) 	<p>Fail Safe/Fail Secure Voltage: 12/24V AC/DC Amps .210 (12V), .105 (24V)</p> <p>EZ FIT™</p>	CX-ED1000	CX-ED1010 CX-ED1850A	CX-ED1020	CX-ED1030	CX-ED1040
SERIES 14 - BHMA GRADE 1 FIRE RATED			Description	Model	Model	Model	Model	
	<p>Designed for use in fire-rated, heavy-duty applications.</p> <p>Accommodates cylindrical locksets with a 5/8" to 3/4" throw (3/4" requires 1/8" door gap) in aluminum, wood or metal frames.</p>	<ul style="list-style-type: none"> UL 1034 burglary-resistant Dual Voltage 12/24V AC/DC Warnock Hersey (90 min.) fire rating Strike depth 1 1/2" Integrated suppressor diode 	<p>Fire Rated/Fail Secure Voltage: 12/24V AC/DC Amps .210 (12V), .105 (24V)</p> <p>EZ FIT™</p>	CX-EL1400	CX-EL1410 CX-EL1450A	CX-EL1420	CX-EL1430	
SERIES 20 - BHMA GRADE 2 STRIKES			Description	Model	Model	Model	Model	Model
	<p>Designed for medium-duty applications. Deep latch cavity accommodates cylindrical locksets with a 5/8" to 3/4" throw (3/4" requires 1/8" door gap) in aluminum, wood or metal frames.</p>	<ul style="list-style-type: none"> UL 1034 burglary-resistant Fail secure and fail safe models Strike depth 1 1/2" Four faceplate options Continuous duty operation (DC) 	<p>Fail Secure 8-16V AC/DC (.350/.485 amps) 16V AC/DC (.700/.970 amps)</p> <p>Fail Secure 12V DC (.210 amps) Fail Secure 24V DC (.105 amps)</p> <p>Fail Safe 12V DC (.210 amps) Fail Safe 24V DC (.105 amps)</p>	CX-EL2001 CX-EL2005 CX-EL2008 CX-EU2005 CX-EU2008	CX-EL2011 CX-EL2015 CX-EL2018	CX-EL2021 CX-EL2025 CX-EL2028	CX-EL2031 CX-EL2035 CX-EL2038	CX-EL2041 CX-EL2045 CX-EL2048 CX-EU2045 CX-EU2048
SERIES 20 - BHMA GRADE 2 PRE LOAD STRIKES			Description	Model	Model	Model	Model	Model
	<p>Designed with the highest pre load rating and 'universal' fail safe/fail secure, 12/24V AC/DC operation. Adjustable keeper and latch monitoring standard.</p> <p>EZ FIT™ model installs in standard ANSI strike plate, and is both vertically and horizontally adjustable.</p>	<ul style="list-style-type: none"> Static Strength 1,500lbs. Selectable 12/24V AC/DC Selectable fail safe/fail secure Adjustable keeper Latch monitoring, standard Pre load (Fail secure only) 	<p>Standard body, Fail Safe/Sec, 12/24V AC/DC, Latch Monitor</p> <p>EZ FIT™, Fail Safe/Sec, 12/24V AC/DC, Latch Monitor</p>	CX-EPD2000L	CX-EPD2010L CX-EPD2850L	CX-EPD2020L	CX-EPD2030L	CX-EPD2040L
SERIES 30 - BHMA GRADE 3 ADJUSTABLE KEEPER			Description	Model	Model	Model	Model	Model
	<p>The latch cavity accommodates cylindrical locksets with a 1/2" to 5/8" throw (5/8" requires 1/8" door gap) in metal, wood or aluminum frames.</p>	<ul style="list-style-type: none"> UL 1034 burglary-resistant Fully reversible for right or left-hand doors Continuous duty operation (DC) Adjustable keeper 	<p>Fail Secure 8-16V AC/DC (.310/.360 amps) 16V AC/DC (.620/.730 amps)</p> <p>Fail Secure 12V DC (.210 amps)</p> <p>Fail Secure 24V DC (.105 amps)</p>	CX-EL3001 CX-EL3005 CX-EL3008	CX-EL3011 CX-EL3015 CX-EL3018	CX-EL3021 CX-EL3025 CX-EL3028	CX-EL3031 CX-EL3035 CX-EL3038	CX-EL3041 CX-EL3045 CX-EL3048
SERIES 22 - BHMA GRADE 2 RIM STRIKES			Description	STRIKES COMPLETE WITH FACEPLATE				
	<p>Designed for rim or surface mounted exit devices for Pullman type latches with up to a 3/4" throw.</p> <p>Horizontal adjustment.</p>	<ul style="list-style-type: none"> UL 1034 burglary-resistant Fail secure Fully reversible for right or left-hand doors Continuous duty operation (DC) 	<p>Fail Secure 12V DC (.210 amps) Fail Secure 24V DC (.105 amps)</p>					CX-EL2255 CX-EL2258