

**LOCKING PRODUCTS** 

## CX-90 / 91 SERIES: SINGLE DOOR MAGNETIC LOCKS

\* SECURITY
UL 103
UL 294
LISTED



**CX-90** (300 Lbs.) and **CX-91** (600 Lbs. & 1200 Lbs.) single door magnetic locks offer the best performance and value. The wide selection of models includes a 'TDS' option with an adjustable timer, lock sensor, door status switch and LED. CX-91 Series magnetic locks are supported with a range of lock mounting accessories, including kits for glass doors. CX-91 Series 600 & 1200 Lbs. magnetic locks are now UL 1034, UL 294, & ULC S533 listed, and are available in an aluminum or black finish.

## **Features**

- 300, 600 and 1,200 Lbs. single door models
- Weather and vandal resistant construction proven over thousands of installations
- · Surface and mortise mount models
- Compatible with all access/egress systems
- Metal mounting jig included on 600 Lbs. and 1200 Lbs. models
- · Locking mounting bolts
- · Field selectable 12/24 VDC operation
- On board MOV power surge protection prevents damage to mag lock
- Wide range of mounting brackets and spacers available
- Lifetime warranty

| MODELS          |  | List Price |  |
|-----------------|--|------------|--|
| 300 Lbs.        |  |            |  |
| CX-90M-03       | 300 Lbs. Mortise Mount Single Door   | \$210.00   |  |
| CX-90S-03       | 300 Lbs. Surface Mount Single Door   | \$210.00   |  |
| 600 Lbs.        |  |            |  |
| CX-91M-06       | 600 Lbs. Mortise Mount Single Door - Basic   | \$220.00   |  |
| CX-91M-06TLS    | 600 Lbs. Mortise Mount Single Door - With Adjustable Timer, Lock Sensor / Relay  | \$260.00   |  |
| CX-91S-06*      | 600 Lbs. Surface Mount Single Door - Basic   | \$220.00   |  |
| CX-91S-06TDS*   | 600 Lbs. Surface Mount Single Door - With Adjustable Timer,<br>Door Status Switch, Lock Sensor / Relay & LED                     | \$290.00   |  |
| CX-91S-06-BK    | 600 Lbs. Surface Mount Single Door - Basic, All-black Finish   | \$260.00   |  |
| CX-91S-06TDS-BK | 600 Lbs. Surface Mount Single Door - With Adjustable Timer,<br>Door Status Switch, Lock Sensor / Relay & LED, All-black Finish   | \$330.00   |  |
| 1200 Lbs.       |  |            |  |
| CX-91S-12*      | 1,200 Lbs. Surface Mount Single Door - Basic   | \$260.00   |  |
| CX-91S-12TDS*   | 1,200 Lbs. Surface Mount Single Door - With Adjustable Timer,<br>Door Status Switch, Lock Sensor / Relay & LED                   | \$310.00   |  |
| CX-91S-12-BK    | 1,200 Lbs. Surface Mount Single Door - Basic, All-black Finish   | \$315.00   |  |
| CX-91S-12TDS-BK | 1,200 Lbs. Surface Mount Single Door - With Adjustable Timer,<br>Door Status Switch, Lock Sensor / Relay & LED, All-black Finish | \$365.00   |  |



## **Specifications**

| Voltage:          | 12/24 VDC   |
|-------------------|---|
| Current Draw:     | CX-90 Series:   |
|                   | 360mA @ 12 VDC<br>180 mA @ 24 VDC                                   |
|                   | CX-91S-06 Series:   |
|                   | 480mA @ 12 VDC  |
|                   | 240mA @ 24 VDC  |
|                   | <b>CX-91S-12 Series:</b> 420mA @ 12 VDC                             |
|                   | 210mA @ 24 VDC  |
| Temp Range:       | 32°F - 131°F (0°C to 55°C)  |
| Contact Rating:   | TDS Models Only   |
|                   | Bond Sensor:  |
|                   | 2A @ 24 VDC<br>Door Status Switch:                                  |
|                   | 0.5A @ 28V AC/DC  |
| Time Delay:       | TDS Version only: 5 - 25 seconds                                    |
| Static Strength:  | CX-91S-06 Series:   |
|                   | 600 lbs. (Factory Tested)<br>500 lbs. (UL Verified)                 |
|                   | CX-91S-12 Series:   |
|                   | 1,200 lbs. (Factory Tested)<br>1000 lbs. (UL Verified)              |
| D                 |   |
| Dynamic Strength: | <b>CX-91S-06 Series:</b> 50 ft-lb <b>CX-91S-12 Series:</b> 70 ft-lb |
| Endurance         |   |
| Endurance:        | 250,000 Cycles  |
| Body Dimensions:  | <b>CX-90S-03:</b> 6-1/2"W x 1-3/8"H x 13/16"D                       |
|                   | (165mm x 35mm x 21mm)   |
|                   | CX-90M-03:  |
|                   | 8"W x 1-3/8"H x 13/16"D   |
|                   | (203mm x 35mm x 21mm)<br><b>CX-91S-06 &amp; CX-91S-06-BK:</b>       |
|                   | 9-7/8"W x 2"H x 1-1/8"D   |
|                   | (250mm x 50mm x 29mm)   |
|                   | <b>CX-91M-06:</b><br>9"W x 1-1/2"H x 1-1/8"D                        |
|                   | (229mm x 38mm x 29mm)   |
|                   | CX-91S-12 & CX-91S-12-BK:   |
|                   | 10-1/2"W x 2-5/8"H x 1-9/16"D<br>(266mm x 67mm x 39mm)              |
|                   | L/DDIIIII X D/IIIII X 39IIIIII                                      |

Armature Plate: **CX-90 Series:** 

5-1/8"W x 1-1/4"H x 1/4"D (130mm x 32mm x 6mm)

**CX-91S-06 Series:** 

7-5/32"W x 1-3/4"H x 15/32"D (182mm x 44mm x 12mm)

CX-91S-12 Series:

7-9/32"W x 2-13/32"H x 5/8"D (185mm x 61mm x 16.5mm)

NEW

NEW